

Böttcherin Flexo-UV

Wash for ANILOX Rollers Used in Flexo Printing

It is suitable for both manual cleaning and use in automatic cleaning systems for ANILOX rollers and machine parts to remove UV inks in flexo printing.

Application

- flash point > 80 °C
- water miscible, free of aromatics, corrosion inhibited
- high wash quality
- good cleaning power for UV inks
- slow evaporation
- economical in use
- non foaming
- good chemical compatibility with UV resistant EPDM rubber rollers
- not suitable for conventional roller compounds

Features

We recommend setting the washing system to optimise the cleaning cycle and Böttcherin Flexo-UV performance. In case of manual cleaning, use Böttcherin Flexo-UV undiluted. Apply the wash to the roller, then finally rinse with water until all ink and cleaning agent residues have been removed.

Note

Follow the automatic washing system manufacturers' operating instructions. If manual cleaning with a hand rag, wear protective gloves during application, follow all press safety instructions.





- 20 litre can
- 200 litre barrel

Package

Böttcherin Flexo-UV is classified according to EC - Directive 1999/45/EC - in its latest version and does not need to be marked. Böttcherin Flexo-UV is not a dangerous good in the sense of national and international transport regulations.

Marking

All our product information sheets, as well as our contact data you will find on the internet www.boettcher-systems.com.

Felix Böttcher GmbH & Co. KG

Headquarter
 Stolberger Str. 351 - 353
 50933 Cologne, Germany
 Phone +49 (0) 221 4907 - 1
 Fax +49 (0) 221 4907 - 435
 koeln@boettcher-systems.com



www.boettcher.de/contact

